


TABELA DE CABO DE AÇO RESISTÊNCIA RUPTURA BITOLA E POLEGADAS CIMAF

 6x19 Seale 1+9+9	DIÂMETRO		MASSA APROXIMADA (kg/m)	CARGA DE RUPTURA MÍNIMA (tf)	
	mm	pol		IPS	EIPS
	3,2	1/8"	0,036	0,61	-
	4,8	3/16"	0,082	1,37	-
	6,4	1/4"	0,142	2,50	2,73
	8,0	5/16"	0,230	3,90	4,30
	9,5	3/8"	0,343	-	6,10
	11,5	7/16"	0,479	-	8,30
	13,0	1/2"	0,608	-	10,80
	14,5	9/16"	0,775	-	13,60
	16,0	5/8"	0,933	-	16,80
	19,0	3/4"	1,298	-	24,00
	22,0	7/8"	1,805	29,50	32,60
	26,0	1"	2,442	38,50	42,60
	29,0	1.1/8"	3,055	-	53,90
	32,0	1.1/4"	3,733	60,10	66,50
	35,0	1.3/8"	4,529	-	80,50
	38,0	1.1/2"	5,328	86,50	95,80
	45,0	1.3/4"	8,368	-	130,40
	52,0	2"	9,740	-	170,30